





Mant's Stereo Viewing Systems Thirde range of inspection and mater

for a wide range of inspection and material rework tasks

- Patented optical technology for fatigue-free viewing and superb image quality
- Wide range of magnification options (to x20)
- Long working distances; large depths of field
- Shadow-free true colour LED illumination

Mantis... Compact, Elite, Macro?

The Mantis family is a unique range of patented optical systems without eyepieces, for intricate tasks requiring superb quality viewing over long periods of time.

Mantis is in use in tens of thousands of sites worldwide and has become the accepted standard for ergonomics and high performance magnification.

The latest generation of Mantis incorporates the most modern advances in optical design, moulded plastics and LED illumination.

Vision Engineering has designed and manufactured world leading optical systems since 1958. The company's patented optical viewers, microscopes and measuring systems are manufactured in Vision Engineering factories in the UK and the USA.

The stereo eyepieceless Mantis viewers have a wide range of applications; it is used throughout manufacturing industries (electronics, precision engineering, plastics, medical devices) and life science laboratories around the world.

Advantages of the next generation Mantis are:

- Entry level, low investment versions
- Compact, functional units
- Wide range of magnification options (to x20)
- Shadow-free LED cold illumination, both surface and substage
- Long working distances; large depths of field
- Stable structures for high magnification viewing







Mantis Compact

Mantis Compact excels in the low magnification range for inspection or manipulation tasks where bench magnifiers have traditionally been used. Mantis Compact has a small footprint and low investment cost giving a superb price / performance ratio.

Mantis Elite

Mantis Elite offers a wider, higher performance specification including high magnification, large field of view, long working distance and head tilt capability. Mantis Elite has enhanced optical performance, making it a perfect alternative to traditional stereo microscopes for a wide range of inspection, preparation and manipulation tasks requiring hand-to-eye co-ordination.

Mantis Macro

Mantis Macro offers a straight through in-line view of the subject, similar in operation to a bench magnifier, but with increased optical clarity and magnification. Mantis Macro offers a comparatively high magnification for an in-line viewer making it ideal for tasks which require exceptional hand-eye coordination and increased magnification.



Mantis Compact is a high value, low investment stereo viewer excelling in the low magnification range for inspection or manipulation tasks where bench magnifiers have traditionally been used.

Patented optical technology allows operators freedom of head movement for superb ergonomics and hand-eye co-ordination, with the ability to wear glasses if required. Operators can increase productivity and improve quality, at an affordable price.




- High value, low investment system
- Superior ergonomics for improved productivity and increased throughput
- Long working distances for easy sample manipulation and rework
- x4, x6 quick change objectives
- Bright white, true colour, LED illumination providing over 10,000 hours of shadow-free viewing
- Superb hand-eye co-ordination for inspection and manipulation tasks
- Patented eyepieceless optics maximise head freedom providing superb ergonomics and reduced eye fatigue
- Choice of stands. Flexible swing arm with small footprint or rigid bench stand for added stability or illumination options



High stability bench stand with integral focus, dimmable substage illumination.

Technical Data



Dimensions:

A = 395mm - 605mm

B = 213mm

C = 565mm - 775mm

D = 90mm - 300mm

E = 335mm - 545mm

Unpacked weight: Head 2.1kg Stand 3.3kg

Packed weight:

Head 4.1kg Stand 4.6kg

| Optical Data | | |
|------------------|------------------|---------------|
| Objective Lenses | Working Distance | Field of View |
| x4 | 96mm | 27.5mm |
| х6 | 73mm | 19.2mm |

Power Supply

9V DC external plug transformer.

Dimensions: A = 526mm - 641mm

B = 305mm

C = 487mm - 602mm

D = 487mm

E = 103mm - 218mm

F = 198mm

G = 123mm

Unpacked weight: Head 2.1kg Stand 4.5kg

Packed weight:

Head 4.1kg Stand 7.9kg

| Lighting Data | | | |
|---|-------------------|--------------|--|
| LUX intensity measured at subject plane with colour correction filters. | | | |
| 20 LEDs | 9,400 LUX | 10,000 hours | |
| Substage illumination (bench stand only) | | | |
| 13 LEDs | 1,200 - 4,000 LUX | 10,000 hours | |
| | | | |

Accessories

Lens protection caps Floating stage (for bench stand) Dust cover Replacement LED array



Mantis Elite is a high performance stereo microscope, offering superb optical performance with magnification options up to x20, making it a perfect alternative to more traditional stereo microscopes.

Large fields of view and generous working distances allow for a wide range of inspection, preparation and manipulation tasks to be carried out, all with exceptional hand-eye co-ordination.




Mantis Elite, with countered-balanced universal stand and 25° tilting head facility, for flexibility and ease of use.

- High value, high specification patented design with superb optical performance
- x4 x20 magnification options with quick change turret allows users to switch between low magnification inspection and high magnification fine detail tasks
- Patented eyepieceless optics maximise head freedom providing superb ergonomics and minimal eye fatigue
- Superior ergonomics for improved productivity and increased throughput
- Superb hand-eye co-ordination for inspection and manipulation tasks
- Bright white, true colour, LED illumination providing over 10,000 hours of shadow-free viewing
- Long working distance and large field of view for easy sample manipulation and rework
- Choice of stands. Flexible swing arm with small footprint or rigid bench stand for added stability or illumination options



High stability bench stand with integral focus, dimmable substage illumination and floating stage option.

Technical Data



Dimensions:

A = 415mm - 624mm

B = 212mm

C = 593mm - 802mm

D = 83mm - 292mm

E = 352mm - 622mm


Unpacked weight: Head 3.0kg Stand 3.3kg

Packed weight: Head 5.0kg Stand 4.6kg

| Optical Data | | |
|------------------|------------------|---------------|
| Objective Lenses | Working Distance | Field of View |
| x4 | 96mm | 34.0mm |
| х6 | 68mm | 23.0mm |
| х8 | 59mm | 17.0mm |
| x10 | 54mm | 13.5mm |
| x15 | 40mm | 8.8mm |
| x20 | 29mm | 6.5mm |

Power Supply

9V DC external plug transformer.



Dimensions:

A = 538mm - 653mm

B = 305mm

C = 496mm - 611mm

D = 487mm

E = 102mm - 217mm

F = 198mm **G** = 172mm

Unpacked weight: Head 3.0kg Stand 4.5kg

Packed weight:

Head 5.0kg Stand 7.9kg

| LUX intensity measured at subject plane with colour correction filters. | | | |
|---|--|--|--|
| X 10,000 hours | | | |
| Substage illumination (bench stand only) | | | |
| LUX 10,000 hours | | | |
| | | | |

Accessories

Lens protection caps Floating stage (for bench stand) Dust cover Replacement LED array



Unlike other Mantis, which have an upright optical path, the Mantis Macro provides straight through in-line viewing which makes the co-ordination of hand and eye even easier.

Mantis Macro offers a straight through in-line view of the subject, similar in operation to a bench magnifier but with increased magnification and optical clarity making it ideal for tasks which require exceptional hand-eye coordination and increased magnification.



Mantis Macro, with countered-balanced universal stand and 30° tilting head facility, for flexibility and ease of use.

- Patented eyepieceless optical technology expands the exit pupil providing head freedom and eye relief for excellent ergonomics
- Straight through in-line optical path offers superb handeye co-ordination for inspection and manipulation tasks
- x2.5 -x5.0 magnification with quick change turret allows user to switch between magnifications
- Superior ergonomics for improved productivity and increased throughput
- Long working distance and large field of view for easy sample manipulation and rework
- Bright white, true colour, LED illumination providing over 10,000 hours of shadow-free viewing





| Technical Data | | |
|----------------|---|--|
| B C | Dimensions: A = 350mm - 570mm B = 170mm C = 500mm - 700mm D = 75mm - 300mm E = 260mm - 450mm F = 20° - 50° | |
| A | Unpacked weight: Head 2.6kg Stand 3.3kg | |
| | Packed weight: Head 4.9kg Stand 4.6kg | |

| Optical Data | | |
|------------------|------------------|---------------|
| Objective Lenses | Working Distance | Field of View |
| x2.5 | 116mm | 48.6mm |
| x5.0 | 66mm | 23.8mm |

| Power Supply | |
|----------------------------------|--|
| 9V DC external plug transformer. | |

| Lighting Data | | |
|---|-----------|--------------|
| LUX intensity measured at subject plane with colour correction filters. | | |
| 40 LEDs | 9,500 LUX | 10,000 hours |

| Accessories | |
|---|--|
| Lens protection caps Dust cover Replacement LED array | |



Vision Engineering manufactures a comprehensive range of ergonomic stand-alone mono and stereo microscopes as well as a complete line of non-contact measuring systems.

For more information...

Vision Engineering has a network of offices and technical distributors around the world. For more information, please contact your Vision Engineering branch, local authorised distributor, or visit our website.

